

LUBE C

*A quality conveyor lubricant with Bio Static Controls
for hard-water areas.*

❖ *BENEFITS*

- ❖ Safe on all container surfaces
- ❖ Concentrated for economy
- ❖ Contains a bacteriostat
- ❖ Provides excellent lubricity

❖ *DESCRIPTION*

LUBE C has been formulated to provide excellent lubricity with a bacteriostat to control microorganisms. The blend of extreme pressure lubricants and fatty acids provide an excellent balance of lubricants to perform under a variety of conditions. It is excellent on steel and Hy Fax conveyors running at either high or low speed.

LUBE C has also been formulated to be compatible with PET bottle, glass, aluminum, or steel containers.

❖ *PROPERTIES*

ODOR.....SOAP
 APPEARANCE.....LIGHT AMBER COLOR
 TOTAL SOLIDS.....36%
 pH OF CONCENTRATION.....8.5-9.5
 SPECIFIC GRAVITY.....1.08

LUBE C

*A quality conveyor lubricant with Bio Static Controls
for hard-water areas.*

❖ *GENERAL USE DIRECTIONS*

In soft water, LUBE C will perform at a rate of 1 part to 300-350 parts of water.

In hard water with hardness up to 17 grains, LUBE C will perform at a rate of 1 part to 150-200 parts of water.

❖ *SAFETY*

DANGER: This is a soap product that contains neutralized fatty acids. Contact with the eye is painful and irritating. Where eye protection when handling this product.

FIRST AID: For eye contact, flush with running water for 15 minutes. Get medical attention if redness or irritation develops. For skin contact, wash with soap and water for several minutes. Get medical attention if irritation develops or persists. If swallowed, drink large amounts of water. Induce vomiting as directed by medical personnel. Call a physician.