

Plicord® Brewline®



APPLICATION:

A quality discharge hose designed specifically for the highly demanding service of transferring non-oily liquid products in wineries and breweries.

CONSTRUCTION:

TUBE: White chlorobutyl rubber (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03)

COVER: Red Versigard® with a white spiral stripe (wrapped impression)

REINFORCEMENT: Spiral-plied synthetic fabric, 4 plies to 1 1/2" I.D.; 6 plies over 1 1/2" I.D.

TEMPERATURE: -40°F to 220°F (-40°C to 104°C)

PACKAGING: 100' length, coiled, polywrapped

BRANDING (SPIRAL): Example: Goodyear® Plicord® Brewline® hose 250 psi; FDA, 3-A, and USDA

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: For special production run minimum requirements, contact customer service.

ID		NOM. OD		MAX. WP		VACUUM HG		WEIGHT	
in.	mm.	in.	mm.	psi.	Mpa.	in.	mm.	lb./ft.	kg./m.
3/4	19.1	1.34	34.0	250	1.72	20	508	0.58	0.80
1	25.4	1.69	42.9	250	1.72	20	508	0.81	1.21
1 1/4	31.8	2.00	50.8	250	1.72	20	508	1.05	1.56
1 1/2	38.1	2.23	56.6	250	1.72	20	508	1.19	1.77
2	50.8	2.88	73.2	250	1.72	20	508	1.86	2.77
2 1/2	63.5	3.51	89.2	250	1.72	20	508	2.66	3.96
3	76.2	4.09	103.9	250	1.72	20	508	3.57	5.31
4	101.6	5.31	134.9	250	1.72	20	508	5.43	8.08