



Premium grade low permeation extra flexible suction and delivery hose suitable for wine and spirits. Phthalates free.

DESCRIPTION

Tube IIR, white. Meets FDA 21 CFR 177.2600, DM 21.03.73 e seguenti and JAPAN-Ministry of Health and Welfare Notice No.370,1959 and No.201, 2006.

Reinforcement Synthetic plies, steel wire helices

Cover Wide corrugated, red, low friction material, non-marking when dragged on the floor, oil, chemical and abrasion resistant, easy to clean.

Sterilization According to 3A Sanitary Standard Class II

Marking TUDERTECHNICA GLIDETECH® VINEYARD

TUDERTECHNICA # **GLIDETECH BUTYL**

TECHNICAL CHARACTERISTICS

Temperature Range -40°F/248°F (-40°C /+120°C)

Vacuum 30.0 Inch HG (0.8 bar)

Norm ISO 1307 for dimensional tolerances
3A Sanitary Standard Class II

CRP Part #	Inside Diameter		Outside Diameter	Working Pressure		Burst Pressure		Appr. Weight		Bending Radius	
	mm	in		in	bar	psi	bar	psi	kg/mt	lbs/ft	mm
8103-075	19	.75	1.22	10	150	30	450	0,69	.49	60	2.36
8103-100	25	1	1.46	10	150	30	450	0,83	.56	70	2.76
8103-150	38	1.5	2.00	10	150	30	450	1,28	.87	80	3.15
8103-200	51	2	2.52	10	150	30	450	1,62	1.10	100	3.94
8103-250	63.5	2.5	3.09	10	150	30	450	2,23	1.52	130	5.12
8103-300	76	3	3.62	10	150	30	450	2,83	1.92	150	5.91
8103-400	102	4	4.65	10	150	30	450	3,76	2.56	250	9.80

Custom colors and sizes available upon request.
Standard Color: Red