

Horizon®

APPLICATION: An economical air and water hose, Horizon is for a wide range of industrial, construction, and agricultural applications. Available in 200, 250, and 300 PSI working pressures.

CONSTRUCTION:

TUBE: Versigard® synthetic rubber, RMA Class C (Limited Oil Resistance)

REINFORCEMENT: Spiral synthetic yarn, 2" is braided

COVER: Black, Red, Yellow, Green or Blue Versigard synthetic rubber



TEMPERATURE: -40°F to 190°F (-40°C to 88°C)

PACKAGING: 3/16"–3/4" 500' reels, maximum 3 pieces, 50' increments. 1" 450' reels, maximum 3 pieces, 50' increments. 1 1/4" 400' reels, maximum 3 pieces, 50' increments. 1 1/2" 300' reels, maximum 3 pieces, 50' increments. 2" 200', cartons, maximum 3 pieces, 50' increments. Coupled assemblies available in 1/4", 3/8", 1/2", and 3/4" in red.

BRANDING: Continuous brand example "1/2" Horizon by Goodyear™XXX psi WP."

COUPLING: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

NON-STOCK/SIZES: Refer to page 300 for special production run minimum requirements.

ORDERING CODE:

Horizon 200

Order Codes: 536-035 (2" black) / 536-040 (2" red) / 569-009 (black) / 569-011 (red) / 569-038 (yellow) / 569-547 (blue)

Id		NOM. OD		MAX. WP		WEIGHT	
in.	mm	in.	mm	psi.	Mpa	lb./ft.	kg./m.
3/16	4.8	0.44	11.2	200	1.38	0.08	0.12
1/4	6.4	0.5	12.7	200	1.38	0.09	0.13
5/16	7.9	0.58	14.7	200	1.38	0.12	0.18
3/8	9.5	0.67	17	200	1.38	0.15	0.22
1/2	12.7	0.81	20.6	200	1.38	0.2	0.3
5/8	15.9	0.97	24.6	200	1.38	0.27	0.4
3/4	19.1	1.12	28.5	200	1.38	0.34	0.51
1	25.4	1.44	36.8	200	1.38	0.54	0.8
1 1/4	31.8	1.73	44	200	1.38	0.75	1.12
1 1/2	38.1	1.98	50.3	200	1.38	0.86	1.28
2	50.8	2.5	63.5	200	1.38	1.16	1.73